

# Thin Client

<b>CPU</b>	<b>VIA C3 CPU</b> <b>VIA C3 800 MHz. Embedded</b>
<b>Core Logic</b>	<b>North Bridge:</b> VIA CLE266 <b>South Bridge:</b> VIA VT8235
<b>Chassis</b>	<b>Type:</b> GBT Small Form Factor (for thin client) <b>Size:</b> 213 (D) x 64 (W) x 234 (H) mm, 3.19 Liter
<b>Memory</b>	<b>Type:</b> DDR 266 <b>Maximum Support:</b> 1GB (Distributor Upgradable) <b>Memory Slot:</b> 1 x 184 Pin DDR
<b>VGA</b>	NA
<b>Audio</b>	<b>Interface:</b> AC97 (on board Codec) 6 channels
<b>BIOS</b>	<b>Type:</b> 2M Flash ROM
<b>HDD</b>	<b>Optional</b> <b>Capacity:</b> NA <b>Interface:</b> PATA (no support in the model for 2.5" HDD)
<b>ODD / FDD</b>	<b>Type:</b> NA
<b>Keyboard/Mouse</b>	<b>Compatible with PS/2 - Keyboard &amp; Mouse</b>
<b>Communication</b>	<b>Modem:</b> N/A <b>Wireless LAN:</b> NA <b>LAN:</b> Built-in 10/100 Base-T Ethernet
<b>I/O Ports</b>	<b>Front:</b> USB x 2, MIC-in x 1, Headphone-out x 1 <b>Rear:</b> PS/2 Keyboard/ Mouse, USB2.0/ 1.1 ports x 2, RJ45 x 1, COM x 2, Audio (Line-in x 1/ Line-out x 1/ MIC x 1), Printer port x 1, VGA port x 1
<b>Flash Card Reader</b>	NA
<b>Power Supply</b>	<b>Power Supply (40W) Ver. 4.0</b>
<b>Others</b>	TBC
<b>Agency</b>	FCC, CE, 3C (To be confirmed with Customer)
<b>Dimensions</b>	213 (D) x 64 (W) x 234 (H) mm
<b>Weight</b>	2 Kg
<b>Architecture</b>	WHQL-certified for Windows edition or Linux compliance

# Thin Client Specifications

## TA 7

<b>CPU (Fanless)</b>	<b>VIA C7 CPU 1.0GHZ</b>
<b>Core Logic</b>	<b>North Bridge:</b> VIA CN700 <b>South Bridge:</b> VT8237R+
<b>Chassis</b>	<b>Type:</b> GBT Small Form Factor. Main Board: Mini-ITX (17*17cm)
<b>Memory</b>	<b>Type:</b> DDR 2 <b>Maximum Support:</b> 1GB (Distributor Upgradeable) <b>Memory Slot:</b> 1xDDR2 DIMM Socket
<b>VGA</b>	Chipset with Built-in enhanced Graphics
<b>Audio</b>	<b>Interface:</b> AC97 Audio Codec-Realtek ALC653
<b>BIOS</b>	<b>Type:</b> 2Mb Flash RAM, AC recovery ON/OFF control, Auto detect & report system health status, AWARD BIOS
<b>HDD</b>	<b>Optional</b> <b>Capacity:</b> NA (IDE1 with pin 20 with 5V power, IDE2 for standard IDE) 2x 20 pin IDE connector
<b>ODD / FDD</b>	<b>Type:</b> NA
<b>Keyboard/Mouse</b>	Compatible with PS/2 – Keyboard & Mouse      Optional
<b>Communication</b>	<b>Modem:</b> N/A <b>Wireless LAN:</b> NA <b>LAN:</b> Built-in 10/100 Base-T Ethernet
<b>I/O Ports</b>	<b>Front:</b> USB x 2, MIC-in x 1, Headphone-out x 1 <b>Rear:</b> PS/2 Keyboard/ Mouse, USB2.0/ 1.1 ports x 4, RJ45 x 1, COM x 1, Audio (Line-in x 1/ Line-out x 1/ MIC x 1), Printer port x 1, VGA port x 1
<b>Flash Card Reader</b>	NA
<b>Power Supply</b>	DC/DC BOARD + 65W ADAPTOR
<b>Others</b>	Support Wake-On-LAN (WOL), Front Line-out and Mic Connector Front Panel Connector (Power Switch, Power LED, HDD LED, LAN activity LED)
<b>EMI/ Safety</b>	FCC Class -B, CE
<b>Dimensions</b>	213 (D) x 64 (W) x 234 (H) mm
<b>Weight</b>	2 Kg
<b>Architecture</b>	WHQL-certified for Windows edition or Linux compliance